





Luminaire Locations			
No.	Label	MH	Orientation
1	A	25.00	297.04
1	C	25.00	105.67
1	E	9.00	169.54
2	E	9.00	23.20
3	E	9.00	46.47
4	E	9.00	18.43
5	E	9.00	201.58
6	E	9.00	197.10
7	E	9.00	216.03
8	E	9.00	249.68
9	E	9.00	222.71
10	E	9.00	213.99
11	E	9.00	80.54
12	E	9.00	180.00
1	G	8.50	63.43
2	G	8.50	151.61
3	G	8.50	246.71
4	G	8.50	334.61
5	G	18.00	334.87
6	G	8.50	65.22
7	G	18.00	248.20
9	G	8.00	67.62
11	G	8.00	335.11
12	G	10.00	250.02
1	H	25.00	25.00
2	H	25.00	20.08
3	H	25.00	70.42

Schedule											
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
	A	1	SPAULDING LIGHTING	CL1-60L-4K-4-BC	CIMARRON CL1	60 LEDs - 4000K - 70 CRI	1	CL1-60L-4K-4-BC.IES	12372	0.9	135
	C	1	SPAULDING LIGHTING	CL1-30L-4K-4-BC	CIMARRON CL1	30 LEDs - 4000K - 70 CRI	1	CL1-30L-4K-4-BC.IES	6308	0.9	70
	E	12	RAB LIGHTING, INC.	GNLED26NSTB/FLOOD REF/FROSTED LENS	CAST FINNED METAL HOUSING, ONE CIRCUIT BOARD WITH ONE LED, SPUN SEMI-SPECULAR METAL REFLECTOR, FROSTED FLAT GLASS LENS IN CAST BLACK PAINTED METAL TRIM RING. LENS FROSTED SIDE UP.	ONE WHITE MULTI-CHIP LIGHT EMITTING DIODE (LED), VERTICAL BASE-UP POSITION.	1	GN1LED26NSTA.ies	1317	0.7	28.5
	G	10	Lithonia Lighting	CSXW LED 30C 1000 40K T4M	CONTOUR SERIES LED WALL-MOUNT WITH 30 4000K LEDS OPERATED AT 100MA AND PRECISION MOLDED ACRYLIC TYPE IV LENS	LED	1	CSXW_LED_30C_1000_40K_T4M.ies	10854	0.9	104
	H	3	SPAULDING LIGHTING	CL1-60L-4K-4-BC	CIMARRON CL1	60 LEDs - 4000K - 70 CRI	1	CL1-60L-4K-4-BC.IES	12372	0.9	270

Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Bldg Area	+	13.3 fc	22.3 fc	7.3 fc	3.1:1	1.8:1
Bldg Area	+	2.6 fc	22.7 fc	0.0 fc	N/A	N/A
Phase 2	+	1.6 fc	11.6 fc	0.0 fc	N/A	N/A
Phase 2 Prkg	+	2.6 fc	27.7 fc	0.5 fc	55.4:1	5.2:1